

Product Technical Information Sheet

Wienerberger Code 24240600
Production Plant Todhills

Manufacture Soft Mud Moulded Stock

Configuration Frogged

Colour Red Multi

Appearance Flat

Work Size (mm) 215 x 102.5 x 65

Pack Quantity 500 No.

Individual Dry Brick Weight (kg) 2.3

Technical Properties to BS EN 771-1

Size Tolerance (Mean/Range) T1/R1
Gross Dry Density (kg/m³/Tolerance) 1630 (D1)

Compressive Strength (N/mm²) ≥20

Thermal Conductivity (W/(m·K)) $\lambda_{10,dry,unit}$ value (EN 1745 tabulated: S1) P=90% 0.60

Durability Designation F2

Water Absorption (%) ≤14

Initial Rate of Water Absorption

Min. 1.2 Max. 2.8

(kg/(m²·min))

Reaction to Fire Class A1

Issue Date: 15/09/2020

Active Soluble Salts

Technical data correct at time of issue. Individual dry brick weights can vary and are for guidance only. Any questions regarding this data should be referred to the Wienerberger Technical Department. Due to the limitations of screen and print colour representation of product images it is advised that brick samples are viewed prior to ordering.







1000+ products to choose from



S2

Expert help and advice



Comprehensive Design Services



Technical Support