

At the heart of building DECLARATION OF PERFORMANCE

Leicester Weathered Multi Stock A0834A

Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.

U for use in Unprotected Masonry

Registered office lbstock Brick Limited. Leicester Road. lbstock Leicestershire. LE67 6HS

Attestation of Conformity System 2+

Notified factory production certification body 1855.CPR/ 24860 **Lucideon CICS Limited** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

Declared Performance Essential Characteristics	Performance		Harmonised Technical Specification	The performance of the product is in conformity with the declared
Dimensions and tolerance mm	215x1 Tolerance Range	T2 R1		performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by:
Configuration Group Flatness of bed faces	Single Frog HD units Group 1 Structural NPD NPD		BS EN771-1:2011/A1:2015	Andy Batterham - Technical & Innovation Director Ibstock Brick
Plane parallelism Compressive Strength (tested normal to the bed face of the unit) N/mm² Dimensional Stability mm/m Bond Strength fixed N/mm² Active Soluble Salts	Mean Normalised Category NF	20 20.4 Cat I	BS EN77 1-1.2011/A1.2019	Limited ALE WIV
Reaction to Fire	S2 Euro Class A1		Commission Decision 2000/605/EC	
Water absorption % Water vapour permeability Direct airborne sound insulation Thermal resistance W/mk Durability against freeze thaw Dangerous substances	19 05-Oct <i>µ</i> 1530 0.8 F2 NPD		BS EN771-1:2011/A1:2015	

Data correct since: 23/02/2022

For data prior to this date please contact technical@ibstock.co.uk Downloaded: 22/8/2022