

EVERBUILD MAMMOTH ALUMINIUM TAPE



| Colour | Product Code | Pack Size | Box Qty |
|--------|--------------|---------------|---------|
| Silver | 2ALUM50 | 50mm x 45Mtr | 24 |
| | 2ALUM75 | 75mm x 45Mtr | 16 |
| | 2ALUM100 | 100mm x 45Mtr | 12 |

Product Description

EVERBUILD Mammoth Aluminium Tape is a heat and light reflective foil tape, heat resistant to 180°C and flame resistant to class O. Excellent moisture resistance, ideal for use as a vapour barrier between foil faced insulation panels in roof and wall applications, duct sealing on all types of air conditioning and ventilation. Protecting wires and pipes from heat.

Benefits

- High temperature resistance.
- Flame retardant to class O.
- Can be used to seal the edges of insulated glass units.

Limitations

- Do not use on surfaces that bleed oils or plasticiser.
- It is the users responsibility to determine suitability for use. If in doubt contact technical services for advice.

Application

Ensure surfaces to which tape is to be applied are clean sound and dry. Remove outer packaging from roll of tape. Peel required amount of tape from roll pressing firmly into place while unrolling. Tear off or cut with a knife when finished.

Specific Data

| | |
|----------------------------------|-----------------------------|
| Adhesive | Hot melt rubber |
| Type Of Film | 30 micron Aluminium foil |
| Tensile Strength | 20.0 N/cm |
| Water Vapour Transmission | 2 gr/ m ² / 24hr |
| Service Temperature | -30°C to +85°C |
| Peel Adhesion | Open 9 N/cm. Closed 9 N/cm |

Storage

Store in cool dry conditions between 5 and 25°C. Safe in normal use however as a precaution keep polythene outer packaging away from children.

Shelf Life

Shelf life 36 months from date of manufacture.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.